



CERTIFICATION

I, Satoko Yamaguchi, of TOYOTA TECHNICAL DEVELOPMENT CORP., 1-21, Imae, Hanamoto-cho, Toyota, Aichi, 470-0334 Japan, hereby certify that I am the translator of the accompanying certified copy of the official communications received from the Japan Patent Office in the patent application identified below, and certify that the following is a true and correct translation to the best of my knowledge and belief.

Application Number

Japanese Patent Application

No.2002-298505


Date of Filing

October 11, 2002

Satoko Yamaguchi
Satoko Yamaguchi

Dated this 19th day of February, 2007

RECEIVED
OLIFF & BERNDT, P.C.
2007 MAR 19 A 10:56



JP-2002-298505

[NAME OF THE DOCUMENT] APPLICATION FOR PATENT

[SERIAL NUMBER] PA14F152

[FILING DATE] October 11, 2002

[ADDRESSEE] Shinichiro OTA
Commissioner of Patent Office

[INT. CL.] H01M 8/04

[INVENTOR]

[DOMICILE OR RESIDENCE] c/o TOYOTA JIDOSHA KABUSHIKI
KAISHA

10 1, Toyota-cho, Toyota-shi, Aichi-ken

[NAME] Shinpei MIURA

[INVENTOR]

[DOMICILE OR RESIDENCE] c/o TOYOTA JIDOSHA KABUSHIKI
KAISHA

15 1, Toyota-cho, Toyota-shi, Aichi-ken

[NAME] Shigeaki MURATA

[APPLICANT]

[ID NUMBER] 000003207

20 [NAME] TOYOTA JIDOSHA KABUSHIKI
KAISHA

[LEGAL REPRESENTATIVE]

[ID NUMBER] 110000028

[NAME] Meisei International Patent Firm

[REPRESENTATIVE] Takashi SHIMOIDE

JP-2002-298505

[PHONE NO.]

052-218-5061

[APPLICATION FEE]

[PAYMENT NUMBER]

133917

[AMOUNT OF PAYMENT]

21, 000 yen

5 [LIST OF ATTACHED DOCUMENTS]

[NAME OF THE DOCUMENT]

Specification

1

[NAME OF THE DOCUMENT]

Drawings

1

[NAME OF THE DOCUMENT]

Abstract

1

[NUMBER OF THE GENERAL POWER OF ATTORNEY]

0105457

10 [REQUIREMENT OF PROOF] Required

[NAME OF THE DOCUMENT] SPECIFICATION

[TITLE OF THE INVENTION] FUEL CELL SYSTEM

[CLAIMS]

[CLAIM 1]

5 A fuel cell system comprising:

a fuel cell;

a fuel gas passage which is connected to the fuel cell and through which a fuel gas containing an odorant and hydrogen gas supplied to the fuel cell flows;

10 an oxidative gas passage which is connected to the fuel cell and through which an oxidative gas supplied to the fuel cell flows;

a fuel off gas passage which is connected to the fuel cell and through which a fuel off gas discharged from the fuel cell flows;

15 an oxidative off gas passage which is connected to the fuel cell and through which an oxidative off gas discharged from the fuel cell flows; and

an odorant removal portion which removes the odorant from the fuel gas after introduction of the fuel gas into the fuel cell.

[CLAIM 2]

The fuel cell system according to claim 1, wherein

20 the odorant is a specific odorant that is unlikely to deteriorate output characteristics of the fuel cell.

[CLAIM 3]

The fuel cell system according to claim 2, wherein

the odorant is butyric acid.

25 [CLAIM 4]

The fuel cell system according to claim 2, wherein

the odorant removal portion is provided in the fuel off gas passage.

[CLAIM 5]

The fuel cell system according to claim 2, further comprising:

30 a circulation system which includes a circulation passage connecting the fuel off gas passage to the fuel gas passage and which causes the fuel gas to circulate,

wherein

the odorant removal portion is provided in the circulation system.

[CLAIM 6]

The fuel cell system according to claim 2, further comprising:

5 a confluent off gas passage into which the fuel off gas passage and the
oxidative off gas passage converge,

wherein

the odorant removal portion is provided in the confluent off gas
passage.

10 [CLAIM 7]

The fuel cell system according to claim 2, wherein

the fuel off gas passage is connected to the oxidative gas passage, and
the odorant removal portion is provided downstream of a connecting
point connecting the fuel off gas passage to the oxidative gas passage.

15 [CLAIM 8]

The fuel cell system according to claim 1, wherein

an internal fuel gas passage through which the supplied fuel gas flows
is formed inside the fuel cell, and

the odorant removal portion is provided in the internal fuel gas
20 passage.

[CLAIM 9]

The fuel cell system according to claim 8, wherein

the fuel cell is provided with a stack including a plurality of electric
cells,

25 the internal fuel gas passage includes a distribution passage which
penetrates the stack and which is designed to distribute the fuel gas to the electric
cells respectively, and

the odorant removal portion is provided in the distribution passage.

[CLAIM 10]

30 The fuel cell system according to claim 8, wherein

the fuel cell is provided with an electric cell,

the internal fuel gas passage includes a fuel gas small passage which is formed on one face of the electric cell and which is designed to supply the electric cell with the fuel gas, and

the odorant removal portion is provided on said one face of the electric cell where the fuel gas small passage is formed.

[CLAIM 11]

The fuel cell system according to claim 1, further comprising:

an oxygen gas supply portion which supplies the odorant removal portion with oxygen gas,

wherein

the odorant removal portion includes a catalyst which promotes oxidation of the odorant.

[DETAILED DESCRIPTION OF THE INVENTION]

[0001]

[TECHNICAL FIELD]

The invention relates to a fuel cell system and, more particularly, to an art for removing an odorant.

[0002]

[RELATED ART]

A fuel cell generates electricity by means of hydrogen gas contained in a fuel gas and oxygen gas contained in an oxidative gas. A spent fuel gas (fuel off gas) and a spent oxidative gas (oxidative off gas) are discharged from the fuel cell.

[0003]

In a fuel cell system, a mixed gas (fuel gas) containing hydrogen gas and an odorant is used to sense leakage of hydrogen gas at an early stage. However, the odorant often deteriorates output characteristics of the fuel cell. Hence, there has been devised a construction wherein an odorant removal portion for removing the odorant from the fuel gas is provided upstream of the fuel cell, more specifically, in a fuel gas passage through which the fuel gas flows. One such fuel cell system is described, for example, in Patent Document 1 disclosed by the applicant of the present application.

[0004]

[Patent Document 1]

Japanese Patent Application Laid-Open No. 2002-29701

[0005]

[PROBLEM TO BE SOLVED BY THE INVENTION]

In such a fuel cell system, however, leakage of hydrogen gas can be sensed only in a fuel gas passage region upstream of a fuel cell.

5

[0006]

The invention has been made to solve the aforementioned problem. It is an object of the invention to provide an art for enlarging a range in which leakage of hydrogen gas can be sensed in a fuel cell.

[0007]

10

[MEANS FOR SOLVING THE PROBLEM AND EFFECTS THEREOF]

15

In order to at least partially solve the problem stated above, a fuel cell system in accordance with the invention comprises a fuel cell, a fuel gas passage which is connected to the fuel cell and through which a fuel gas containing an odorant and hydrogen gas supplied to the fuel cell flows, an oxidative gas passage which is connected to the fuel cell and through which an oxidative gas supplied to the fuel cell flows, a fuel off gas passage which is connected to the fuel cell and through which a fuel off gas discharged from the fuel cell flows, an oxidative off gas passage which is connected to the fuel cell and through which an oxidative off gas discharged from the fuel cell flows, and an odorant removal portion which removes from the fuel gas the odorant after introduction of the fuel gas into the fuel cell.

20

[0008]

25

With this system, the odorant removal portion can remove the odorant after the fuel gas has been introduced into the fuel cell. Therefore, it is possible to at least sense leakage of hydrogen gas from the fuel gas passage and leakage of hydrogen gas from the fuel cell. That is, employing this system makes it possible to enlarge an area in which leakage of hydrogen gas can be sensed.

[0009]

30

In the system described above, the odorant may be a specific odorant that is unlikely to deteriorate output characteristics of the fuel cell.

[0010]

Thus, it is possible to inhibit output characteristics of the fuel cell from deteriorating due to the odorant. Therefore, it is possible to enhance a degree of freedom in disposing the odorant removal portion.

[0011]

For example, the odorant may be butyric acid.

[0012]

In the system described above, the odorant removal portion may be provided in the fuel off gas passage.

5 [0013]

Thus, it is possible to sense leakage of hydrogen gas from the fuel off gas passage at a portion upstream of the odorant removal portion.

[0014]

10 The system described above may further include a circulation system which includes a circulation passage connecting the fuel off gas passage to the fuel gas passage and which causes the fuel gas to circulate. The odorant removal portion may be provided in the circulation system.

[0015]

15 Thus, it is also possible to sense leakage of hydrogen from the fuel off gas passage at a position upstream of the odorant removal portion. It is also possible to suppress a gradual increase in the concentration of the odorant in the circulating fuel gas

[0016]

20 The system described above may further include a confluent off gas passage into which the fuel off gas passage and the oxidative off gas passage converge. The odorant removal portion may be provided in the confluent off gas passage.

[0017]

25 Thus, it is also possible to sense leakage of hydrogen gas from the fuel off gas passage. Because the fuel off gas is mixed with the oxidative off gas, it is also possible to reduce a concentration of hydrogen gas contained in the discharged gas. In addition, if the odorant enters the oxidative off gas passage through the fuel cell, the odorant that has been mixed with the oxidative off gas can also be removed.

[0018]

30 In the system described above, the fuel off gas passage may be connected to the oxidative gas passage. The odorant removal portion may be provided downstream of a connecting point connecting the fuel off gas passage to the oxidative gas passage.

[0019]

Thus, it is also possible to sense leakage of hydrogen gas from the fuel off gas passage. Because the fuel off gas is mixed with the oxidative off gas, it is also possible to reduce a concentration of hydrogen gas contained in the discharged gas.

5

[0020]

In the system described above, an internal fuel gas passage through which the supplied fuel gas flows may be formed inside the fuel cell, and the odorant removal portion may be provided in the internal fuel gas passage.

[0021]

10

Thus, it is possible to sense leakage of hydrogen gas from the fuel cell. Further, a space for providing the odorant removal portion need not be prepared outside the fuel cell.

[0022]

15

In the system described above, the fuel cell may be provided with a stack including a plurality of electric cells, the internal fuel gas passage may include a distribution passage which penetrates the stack and which is designed to distribute the fuel gas to the electric cells respectively, and the odorant removal portion may be provided in the distribution passage.

[0023]

20

In the system described above, the fuel cell may be provided with an electric cell, the internal fuel gas passage may include a fuel gas small passage which is formed on one face of the electric cell and which is designed to supply the electric cell with the fuel gas, and the odorant removal portion may be provided on said one face of the electric cell where the fuel gas small passage is formed.

25

[0024]

Thus, it is possible to use the odorant that is likely to deteriorate the output characteristics of the fuel cell.

[0025]

30

The system described above may further include an oxygen gas supply portion which supplies the odorant removal portion with oxygen gas. The odorant removal portion may include a catalyst which promotes oxidation of the odorant.

[0026]

Thus, the odorant removal portion can oxidize the odorant.

[0027]

Note that, the invention can be realized in various embodiments, for example, a fuel cell system, and an apparatus such as a movable body in which the fuel cell system is mounted.

[0028]

[EMBODIMENTS OF THE INVENTION]

A. First embodiment:

A-1. Overall Construction of Fuel Cell System:

Next, modes of implementing the invention will be described on the basis of embodiments thereof. Fig. 1 is an explanatory view showing an overall construction of a fuel cell system in accordance with the first embodiment. This fuel cell system is installed in a vehicle.

[0029]

As shown in Fig. 1, a fuel cell system includes a fuel cell 100, a fuel gas supply portion 200 for supplying the fuel cell with a fuel gas containing hydrogen gas, an oxidative gas supply portion 300 for supplying the fuel cell with an oxidative gas (air) containing oxygen gas, and a control portion 600 for controlling operation of the entire fuel cell system. A fuel gas passage 201 through which a fuel gas supplied from the fuel gas supply portion 200 flows and a fuel off gas passage 202 through which a spent fuel off gas flows are connected to the fuel cell 100. Further, an oxidative gas passage 301 through which an oxidative gas supplied from the oxidative gas supply portion 300 flows and an oxidative off gas passage 302 through which a spent oxidative off gas flows are connected to the fuel cell 100. The fuel off gas passage 202 and the oxidative off gas passage 302 converge in their downstream regions into a confluent off gas passage 401.

[0030]

The fuel cell 100 (Fig. 1) is a polymer electrolyte fuel cell which is relatively small in size and exhibits excellent efficiency in generating electricity. Fig. 2 is an explanatory view schematically showing an electric cell structure inside the fuel cell 100 shown in Fig. 1. As shown in Fig. 2, the fuel cell 100 includes a plurality of laminated electric cells (single cells) 110. Each of separators 120 is disposed between two adjacent ones of the single cells.




[0031]

Each of the single cells 110 includes an electrolyte membrane 112, an anode (hydrogen pole) 114a, and a cathode (oxygen pole) 114c. The electrolyte membrane 112 is sandwiched between the two electrodes 114a and 114c. Each of the separators 120 is so disposed as to be in contact with the anode 114a of one of two adjacent ones of the single cells and with the cathode 114c of the other single cell. A plurality of grooves are formed in both faces of each of the separators 120. A plurality of small passages 121 are formed between the anode 114a and each of the separators 120, whereas a plurality of small passages 122 are formed between the cathode 114c and each of the separators 120.

10 [0032]

A fuel gas containing hydrogen gas is supplied to the anode (hydrogen pole)-side passages 121 from the fuel gas supply portion 200, whereas an oxidative gas containing oxygen gas is supplied to the cathode (oxygen pole)-side passage 122 from the oxidative gas supply portion 300. An electrochemical reaction shown below progresses.

[0033]



20 [0034]

A formula (1) shows a reaction in the anode 114a. A formula (2) shows a reaction in the cathode 114c. A formula (3) progresses on the whole. Water (water vapor) generated in the cathode 114c is referred to as "water product" as well.

[0035]

25 The electrolyte membrane 112 is a positive ion exchange resin membrane exhibiting good electrical conductivity in a wet state. As the positive ion exchange resin membrane, a membrane formed of a solid polymer material such as fluororesin or the like can be used. For instance, Nafion® (manufactured by Du Pont Co., Ltd.) can be used. The anode 114a and the cathode 114c are formed of materials exhibiting sufficient gas diffusibility and sufficient electrical conductivity. These materials include carbon cloth, carbon paper, carbon felt and the like, which are manufactured by weaving carbon fiber. Catalytic layers 116a and 116c, which cause reactions in the electrodes 114a and 114c at a relatively low temperature (from about 50°C to about 100°C) respectively, are formed in an interface between the electrode 114a and the

electrolyte membrane 112 and in an interface between the electrode 114c and the electrolyte membrane 112, respectively. As an example of catalysts, Pt or an alloy containing Pt can be used. The separators 120 are formed of a material exhibiting sufficient gas impermeability, sufficient electrical conductivity, and sufficient corrosion resistance. This material is press-formed carbon, a metal or the like.

[0036]

As described above, the fuel cell 100 generates electricity by means of hydrogen gas contained in the fuel gas supplied from the fuel gas supply portion 200 and oxygen gas contained in the oxidative gas (air) supplied from the oxidative gas supply portion 300.

[0037]

The fuel gas supply portion 200 (Fig. 1) includes a gas tank 210, a pressure reducing valve 221, and a flow control valve 222. The gas tank 210 stores a mixed gas (fuel gas) containing hydrogen gas and an odorant at a relatively high pressure. The pressure reducing valve 221 reduces the fuel gas supplied from the gas tank 210 to a predetermined pressure. The flow control valve 222 adjusts a flow rate of the fuel gas and supplies it to the fuel cell 100.

[0038]

The fuel gas supply portion 200 further includes a gas-liquid separation portion 240, a circulating pump 250, and a shut-off valve 260. The gas-separation portion 240, the circulating pump 250, and the shut-off valve 260 are arranged in this order along the fuel off gas passage 202. The fuel off gas passage 202 and the fuel gas passage 201 are connected by a circulation passage 203. More specifically, the circulation passage 203 is connected to the fuel off gas passage 202 at a first connecting point C1 between the circulating pump 250 and the shut-off valve 260, and is connected to the fuel gas passage 201 at a second connecting point C2 downstream of the flow control valve 222.

[0039]

The circulating pump 250 has a function of returning a fuel off gas containing a relatively low concentration of hydrogen gas into the fuel gas passage 201 as a fuel gas. Because of this construction, the fuel gas circulates through an annular passage. By thus causing the fuel gas to circulate, it becomes possible to increase a flow rate (mol/sec) of hydrogen gas supplied into the fuel cell 100 per unit time. As a result, reaction efficiency in the fuel cell 100 can be enhanced. However,

as the electrochemical reaction in the fuel cell 100 progresses, the amount (mol) of hydrogen gas contained in the fuel gas in the annular passage decreases. Nitrogen gas, water vapor (water product) and the like contained in the oxidative gas in the cathode-side passage 122 enter the fuel gas in the anode-side passage 121 via the electrolyte membrane 112 inside the fuel cell 100. Therefore, the concentration (volume percentage) of hydrogen gas contained in the fuel gas gradually decreases. In this embodiment, therefore, the flow control valve 222 and the shut-off valve 260 are so set as to be opened intermittently. Thus, the fuel gas containing a high concentration of hydrogen gas is supplied to the fuel cell 100, whereas the fuel off gas containing a low concentration of hydrogen gas is discharged from the fuel cell 100. The gas-liquid separation portion 240 has a function of removing excessive water vapor from the fuel off gas.

[0040]

The fuel off gas passage 202 is provided with an odorant removal portion 510. The odorant removal portion 510 has a function of removing an odorant from the fuel off gas. The fuel off gas which has been discharged from the odorant removal portion 510 and which contains almost no odorant is discharged to the atmosphere via the fuel off gas passage 202 and the confluent off gas passage 401. The odorant removal portion 510 will be described later in more detail.

[0041]

The oxidative gas supply portion 300 is provided with an air blower 310. The oxidative gas supply portion 300 supplies the oxidative gas (air) containing oxygen gas to the fuel cell 100 via the oxidative gas passage 301. The spent oxidative off gas is discharged to the atmosphere via the oxidative off gas passage 302 and the confluent off gas passage 401.

[0042]

A-2. Construction of Odorant Treatment Portion:

Fig. 3 is an explanatory view showing an internal structure of the odorant removal portion 510 shown in Fig. 1. The odorant removal portion 510 includes a carrier 512 having a plurality of corrugated small passages. An adsorbent is carried on the carrier 512.

[0043]

Fig. 4 is an explanatory view showing a method of manufacturing the odorant removal portion 510 shown in Fig. 3. As shown in Fig. 4, the carrier 512 is

formed of a sheet composed of a flat plate 512a and a corrugated plate 512b. The sheet is joined at one end thereof to an axial member 512c. Then, the sheet is spirally wound around the axial member, which serves as a core. That is, the carrier 512 (Fig. 3) has a roll structure in which the flat plate 512a and the corrugated plate 512b are alternately wound around the axial member 512c. The distance between adjacent portions of the flat plate 512a is held substantially constant by the corrugated plate 512b. Formed between the flat plate 512a and the corrugated plate 512b are a plurality of corrugated small passages, which extend along an axial direction of the axial member 512c. After the carrier 512 has been prepared, an adsorbent is carried on the carrier 512. For instance, the carrier 512 is soaked in a solution containing the adsorbent and then is baked, whereby the adsorbent is fixed onto the carrier 512.

[0044]

A metal material such as stainless steel or the like can be used as the flat plate 512a and the corrugated plate 512b. A porous material such as activated carbon, zeolite or the like can be used as the adsorbent. Although the carrier 512 has a roll structure in the first embodiment, the carrier 512 may have a honeycomb structure instead.

[0045]

As described above, the odorant removal portion 510 contains the adsorbent. Therefore, the adsorbent adsorbs the odorant in the fuel off gas, whereby it becomes possible to remove the odorant from the fuel off gas. The odorant is physically adsorbed into micropores of the adsorbent.

[0046]

In the related art, t-butyl mercaptan (TBM) containing sulfur is used as the odorant. If an odorant containing sulfur, for example, TBM or the like is used in the system shown in Fig. 1, output characteristics of the fuel cell is likely to deteriorate. This is because the catalyst inside the fuel cell is likely to be poisoned due to the odorant.

[0047]

In the first embodiment, therefore, a specific odorant that makes output characteristics of the fuel cell unlikely to deteriorate is used as the odorant. More specifically, butyric acid is used in the first embodiment. Butyric acid is unlikely to poison the catalyst inside the fuel cell, and therefore is unlikely to deteriorate output characteristics of the fuel cell. Thus, by using butyric acid as the odorant, it becomes

possible to provide the odorant removal portion 510 downstream of the fuel cell 100, more specifically, in the fuel off gas passage 202. Butyric acid that is used as the odorant has properties which make output characteristics of the fuel cell unlikely to deteriorate. Therefore, the odorant removal portion 510 can be provided downstream of the fuel cell. Thus, it is possible to sense not only leakage of hydrogen gas from the fuel gas passage 201 upstream of the fuel cell 100 but also leakage of hydrogen gas from a connecting portion between the fuel cell 100 and the fuel gas passage 201 or from the interior of the fuel cell.

[0048]

As described hitherto, the fuel cell system of the first embodiment includes the fuel cell 100, the fuel gas passage 201, the oxidative gas passage 301, the fuel off gas passage 202, the oxidative off gas passage 302, and the odorant removal portion 510 provided in the fuel off gas passage 202. In order to remove the odorant after introduction of the fuel gas into the fuel cell 100, the odorant removal portion 510 can sense leakage of hydrogen gas from the fuel gas passage 201, leakage of hydrogen gas from the fuel cell 100, and leakage of hydrogen gas from the fuel off gas passage at a portion upstream of the odorant removal portion 510. That is, adoption of the construction of the first embodiment makes it possible to enlarge a range where leakage of hydrogen gas can be sensed.

[0049]

In the first embodiment, the circulating pump 250 is provided in the fuel off gas passage 202. Instead, however, the circulating pump 250 may be provided in the circulation passage 203.

[0050]

In the first embodiment, the fuel off gas passage 202 and the oxidative off gas passage 302 are connected in their downstream regions to the confluent off gas passage 401. However, the confluent off gas passage 401 can be omitted. However, the construction of the first embodiment wherein the fuel off gas and the oxidative off gas are mixed with each other is advantageous in that the concentration (volume percentage) of hydrogen gas contained in the mixed gas discharged to the atmosphere can be reduced.

[0051]

B. Second Embodiment:

Fig. 5 is an explanatory view showing an overall construction of a fuel cell system in accordance with the second embodiment. Although Fig. 5 is substantially identical with Fig. 1, disposal of the odorant removal portion 520 has been modified. To be more specific, although the odorant removal portion 510 is provided in the fuel off gas passage 202 downstream of the shut-off valve 260 in Fig. 1, the odorant removal portion 520 is provided in the fuel off gas passage 202 between the circulating pump 250 and the first connecting point C1 in Fig. 5.

[0052]

Even in the case where the construction shown in Fig. 5 is adopted, it is possible to sense leakage of hydrogen gas from the fuel gas passage 201, leakage of hydrogen gas from the fuel cell 100, and leakage of hydrogen gas from the fuel off gas passage at a portion upstream of the odorant removal portion 520.

[0053]

In the case where the fuel off gas is caused to circulate, the concentration (volume percentage) of the odorant contained in the fuel gas gradually increases in the annular passage. As shown in Fig. 5, however, according to the construction wherein the odorant removal portion 520 is disposed in the annular passage, the odorant removal portion 520 can remove the odorant in the annular passage. Therefore, the concentration of the odorant contained in the fuel gas can be inhibited from increasing in the annular passage.

[0054]

In Fig. 5, the odorant removal portion 520 is provided between the circulating pump 250 and the first connecting point C1. Instead, however, the odorant removal portion 520 may be provided between the gas-liquid separation portion 240 and the circulating pump 250. In Fig. 5, the odorant removal portion 520 is provided in the fuel off gas passage 202. Instead, however, an odorant removal portion may be provided in the circulation passage 203.

[0055]

In general, in the case where a fuel cell system includes a circulation passage for connecting a fuel off gas passage to a fuel gas passage and is equipped with a circulation system for causing a fuel gas to circulate, it is appropriate that an odorant removal portion be provided in the circulation system. In Fig. 5, the circulation system includes a passage extending from the fuel cell to the first connecting point C1 (i.e., an upstream portion of the fuel off gas passage) and a

passage extending from the first connecting point to a second connecting point C2 (i.e., the circulation passage).

[0056]

C. Third Embodiment:

5 Fig. 6 is an explanatory view showing an overall construction of a fuel cell system in accordance with the third embodiment. Although Fig. 6 is substantially identical with Fig. 1, the confluent off gas passage 401 is omitted, and an air blower 290 is added. The air blower 290 is connected to the fuel off gas passage 202 at a third connecting point C3 downstream of the shut-off valve 260, and introduces air
10 into the fuel off gas passage 202. The air that has been introduced into the fuel off gas passage 202 is supplied to an odorant removal portion 530.

[0057]

 Even in the case where the construction shown in Fig. 6 is adopted, the concentration (volume percentage) of hydrogen gas contained in the fuel off gas
15 discharged to the atmosphere can be reduced by means of air supplied from the air blower 290.

[0058]

C-1. First Modification Example of Third Embodiment:

 Fig. 7 is an explanatory view showing an overall construction of a fuel
20 cell system in accordance with a first modification example of the third embodiment. Although Fig. 7 is substantially identical with Fig. 6, disposal of the odorant removal portion 530A has been modified. More specifically, although the odorant removal portion 530 is provided in the fuel off gas passage 202 in Fig. 6, an odorant removal portion 530A is provided inside a fuel cell 100C in Fig. 7. In
25 Fig. 7, the fuel off gas passage 202 is connected to the oxidative gas passage 301, and the air blower 290 is omitted.

[0059]

 Fig. 8 is an explanatory view schematically showing an internal construction of the fuel cell shown in Fig. 7. As shown in Fig. 8, the fuel cell 100C
30 includes three stacks 101 to 103, a plurality of first branch pipes 131 for distributing an oxidative gas to the stacks respectively, and a plurality of second branch pipes 132 for gathering oxidative off gases flowing from the stacks respectively. As described with reference to Fig. 2, each of the stacks 101 to 103 includes a plurality of laminated single cells. The first branch pipes 131 include an upstream-side basal

passage and downstream-side three partial passages, and the partial passages are connected to the respective stacks 101 to 103. The first branch pipes 131 are connected to the oxidative gas passage 301 via an oxidative gas supply port 301p. Similarly, the second branch pipes 132 include upstream-side three partial passages and a downstream-side basal passage, and the partial passages are connected to the respective stacks 101 to 103. The second branch pipes 132 are connected to the oxidative off gas passage 302 via an oxidative off gas discharge port 302p. The odorant removal portion 530A is provided in the basal passage of the first branch pipes 131.

10 [0060]

If the construction shown in Figs 7 and 8 is adopted, it is possible to sense leakage of hydrogen gas from the fuel gas passage 201, leakage of hydrogen gas from the fuel cell 100C, and leakage of hydrogen gas from the fuel off gas passage 202. Further, the air blower 290 shown in Fig. 6 can be omitted, and the concentration (volume percentage) of hydrogen gas contained in the mixed off gas discharged to the atmosphere can be reduced by means of the oxidative gas (air) supplied from the air blower 310 included in the oxidative gas supply portion 300. In addition, since a space for providing the odorant removal portion need not be prepared outside the fuel cell, an existent fuel cell system can be relatively easily substituted for.

20 [0061]

In Fig. 8, the odorant removal portion 530A is provided in the basal passage of the first branch pipes 131. Instead, however, it is also appropriate that the odorant removal portion 530A be provided in each of three partial passages. In Fig. 8, the odorant removal portion 530A is provided in the first branch pipes 131. Instead, however, it is also appropriate that the odorant removal portion 530A be provided in the second branch pipes 132. In general, if a fuel off gas passage is connected to an oxidative gas passage, it is appropriate that an odorant removal portion be provided downstream of a connecting point between the fuel off gas passage and the oxidative gas passage.

30 [0062]

C-2. Second Modification Example of Third Embodiment:

In Fig. 6, the air blower 290 supplies air (oxygen gas) to the odorant removal portion 530. In Fig. 7, the air blower 310 supplies air (oxygen gas) to the odorant removal portion 530A. In these cases, it is preferable that the odorant

removal portion be equipped with a porous adsorbent and a catalyst for promoting oxidation of an odorant. As the catalyst, a noble metal catalyst such as Pt, Pd, Ru or the like can be used. The odorant removal portion as mentioned above can be prepared, for example, by soaking the carrier 512 shown in Fig. 3 in a solution containing an adsorbent and a catalyst and then baking the carrier 512.

[0063]

If the odorant removal portion includes only a porous adsorbent, there is a limit to the amount of an odorant that can be adsorbed by the odorant removal portion. The speed at which the odorant removal portion adsorbs the odorant decreases as the amount of the adsorbed odorant increases. As described above, however, if the odorant removal portion includes a porous adsorbent and a noble metal catalyst, the odorant removal portion can oxidize (burn) the physically adsorbed odorant by means of oxygen gas contained in supplied air. Accordingly, it is possible to recover adsorption capacity, which deteriorates as the amount of the adsorbed odorant increases. As a result, replacement of an odorant treatment portion can be omitted.

[0064]

C-3. Third Modification Example of Third Embodiment:

In the case where the odorant removal portions 530 and 530A are supplied with air (oxygen gas) as shown in Figs. 6 and 7, they may include a catalyst for promoting oxidation of an odorant instead of a porous adsorbent. As the catalyst, a noble metal catalyst such as Pt, Pd, Ru or the like can be used. This odorant removal portion can be prepared, for example, by soaking the carrier 512 shown in Fig. 3 in a solution containing the catalyst and then baking the carrier 512.

[0065]

This odorant removal portion can oxidize (burn) the odorant contained in the fuel off gas by means of oxygen gas contained in supplied air. That is, even in the case where this odorant removal portion is adopted, the odorant can be removed from the fuel off gas, and replacement of the odorant treatment portion can be omitted.

[0066]

As described with reference to Fig. 2, the catalyst 116c containing a noble metal such as Pt or the like is formed in the interface between the cathode 114c and the electrolyte membrane 112 of the fuel cell. Hence, if the construction shown in Fig. 7 is adopted, the odorant can be oxidized in the cathode-side passage 122 as well.

[0067]

D. Fourth Embodiment:

Fig. 9 is an explanatory view showing an overall construction of a fuel cell system in accordance with the fourth embodiment. Although Fig. 9 is substantially identical with Fig. 1, disposal of the odorant removal portion 540 has been modified. More specifically, although the odorant removal portion 510 is provided in the fuel off gas passage 202 in Fig. 1, the odorant removal portion 540 is provided in the confluent off gas passage 401 in Fig. 9.

[0068]

If the construction shown in Fig. 9 is adopted, it is possible to sense leakage of hydrogen gas from the fuel gas passage 201, leakage of hydrogen gas from the fuel cell 100, and leakage of hydrogen gas from the fuel off gas passage 202. Further, since the fuel off gas is mixed with the oxidative off gas, it is also possible to reduce a concentration (volume percentage) of hydrogen gas contained in the mixed off gas discharged to the atmosphere.

[0069]

The odorant contained in the fuel gas may enter the cathode-side passage 122 from the anode-side passage 121 via the electrolyte membrane 112 (Fig. 2) inside the fuel cell 100. In the case where the construction shown in Fig. 1 is adopted, the odorant that has entered the oxidative off gas is directly discharged to the atmosphere. However, in the case where the construction shown in Fig. 9 is adopted, the odorant removal portion 540 can remove both the odorant contained in the fuel off gas and the odorant that has entered the oxidative off gas.

[0070]

The oxidative off gas contains oxygen gas that has not been used in the electrochemical reaction in the fuel cell 100. Accordingly, as described in the second and third modification examples of the third embodiment, the odorant removal portion may also include a noble metal catalyst. Thus, the odorant removal portion can oxidize the odorant.

[0071]

In Fig. 9, the odorant removal portion 540 is provided only in the confluent off gas passage 401. However, an additional odorant removal portion may be provided in the fuel off gas passage 202.

[0072]

D-1. Modification Example of Fourth Embodiment:

Fig. 10 is an explanatory view showing an overall construction of a fuel cell system in accordance with a modification example of the fourth embodiment. Although Fig. 10 is substantially identical with Fig. 9, an odorant removal portion 542 has been added to the interior of a fuel cell 100D.

5 [0073]

Fig. 11 is an explanatory view schematically showing an electric cell structure inside the fuel cell 100D shown in Fig. 10. Fig. 11 is substantially identical with Fig. 2. Instead of the catalytic layer 116c, however, the odorant removal portion 542 containing a porous adsorbent and a noble metal catalyst is formed in the
10 interface between the electrolyte membrane 112 and the cathode 114c.

[0074]

If the construction shown in Fig. 11 is adopted, the odorant removal portion 542 can physically adsorb an odorant that is about to enter the cathode-side passage 122 via the electrolyte membrane 112, and can oxidize (burn) the physically
15 adsorbed odorant by means of oxygen gas contained in the supplied oxidative gas (air).

[0075]

E. Fifth Embodiment:

In the first to fourth embodiments, butyric acid is used as the odorant. In
20 the fifth embodiment, however, t-butyl mercaptan (TBM) is used as the odorant. As described above, an odorant containing sulfur, for example, TBM or the like poisons the catalyst inside the fuel cell, so that output characteristics of the fuel cell deteriorate.

[0076]

25 In the fuel cell system of the fifth embodiment, even in the case where an odorant that is likely to deteriorate output characteristics of the fuel cell is used, a contrivance has been made such that a fuel gas containing the odorant can be introduced into the fuel cell. Thus, instead of TBM, tetrahydrothiophene (THT), dimethyl sulfide (DMS), methyl mercaptan, ethyl mercaptan or the like can be used as
30 an odorant that is likely to deteriorate output characteristics of the fuel cell.

[0077]

Fig. 12 is an explanatory view showing an overall construction of a fuel cell system in accordance with the fifth embodiment. In Fig. 12, an odorant removal portion 550 is provided inside the fuel cell 100E.

[0078]

Fig. 13 is an explanatory view schematically showing a stack structure inside the fuel cell 100E shown in Fig. 12. As shown in Fig. 13, a stack 101E includes a plurality of laminated single cells 110. The stack 101E is provided with three pairs of distribution passages, which penetrate the stack. The first pair of the distribution passages H1a and H1b communicates with the anode-side passage 121 formed in one face of each of the separators 120. The fuel gas that has been introduced from an opening portion of the fuel cell is distributed to the respective single cells via the distribution passages H1a and H1b. The second pair of the distribution passages H2a and H2b communicates with the cathode-side passage formed in the other face of each of the separators 120, and distributes the oxidative gas to the respective single cells. The third pair of the distribution passages H3a and H3b communicates with a cooling passage formed in each of specific ones of the separators, and distributes coolant thereto. Each of these specific separators exists among a certain number of the separators.

[0079]

In Fig. 13, the odorant removal portion 550 is provided on a wall of the first distribution passage H1a. The odorant is removed from the fuel gas in the first distribution passage H1a. Hence, the odorant does not enter the single cells 110 (more specifically, the catalytic layer 116a between the electrolyte membrane 112 and the anode 114a shown in Fig. 2). As a result, the catalyst inside the fuel cell can be inhibited from being poisoned. The first distribution passage H1a may have a honeycomb structure. Thus, the area for forming the odorant removal portion can be increased. Therefore, the odorant can be removed more reliably.

[0080]

E-1. First Modification Example of Fifth Embodiment:

Fig. 14 is an explanatory view schematically showing an electric cell structure inside a fuel cell 100E1 in accordance with a first modification example of the fifth embodiment. Although Fig. 14 is substantially identical with Fig. 2, an odorant removal portion 550A is additionally disposed on the anode 114a. The odorant removal portion 550A can be obtained, for example, by applying a porous adsorbent on the anode 114a and baking the adsorbent.

[0081]

In Fig. 14, the odorant removal portion 550A is provided on the anode 114a, namely, on one face of each of the single cells 110 where the anode-side passages 121 are formed. The odorant is removed from the fuel gas in the anode-side passages 121. Hence, the odorant does not enter the single cells 110 (more specifically, the catalytic layer 116a between the electrolyte membrane 112 and the anode 114a). As a result, the catalyst inside the fuel cell can be inhibited from being poisoned.

[0082]

If the construction shown in Figs. 13 and 14 is adopted, it is possible to sense leakage of hydrogen gas from the interiors of the fuel cells 100E and 100E1. It is also possible to use an odorant that is unlikely to deteriorate output characteristics of the fuel cell.

[0083]

E-2. Second Modification Example of Fifth Embodiment:

In Figs. 12 to 14, TBM is used as the odorant. Instead, however, butyric acid can also be used. In this case, the odorant removal portion may be provided somewhere else inside the fuel cell. For instance, the odorant removal portion 550 is provided on the wall of the first distribution passage H1a in Fig. 13. Instead, however, the odorant removal portion may be provided on a wall for forming the anode-side passages 121 of each of the separators, or on a wall of the second distribution passage H1b. Alternatively, an additional odorant removal portion may be provided on the wall for forming the anode-side passages 121 of each of the separators, or on the wall of the second distribution passage H1b. In the case where the fuel cell includes a plurality of stacks, the odorant removal portion may be provided in a plurality of branch pipes for distributing the fuel gas to the respective stacks, or in a plurality of branch pipes (see Fig. 8) for gathering the fuel off gas flowing from the respective stacks. Thus, if an odorant that is unlikely to deteriorate output characteristics of the fuel cell is used, the output characteristics of the fuel cell can be inhibited from deteriorating due to the odorant. Thus, a degree of freedom in disposing the odorant removal portion can be enhanced.

[0084]

In general, an internal fuel gas passage through which a supplied fuel gas flows is formed in a fuel cell, and it is appropriate that an odorant removal portion be provided in the internal fuel gas passage. Thus, leakage of hydrogen gas from the

interior of the fuel cell can be sensed. Further, a space for providing the odorant removal portion need not be prepared outside the fuel cell. Therefore, this construction is advantageous in that an existent fuel cell system can be relatively easily substituted for, and in that the fuel cell system can be reduced in size.

5 [0085]

In the case where butyric acid is used as the odorant, the odorant removal portion may include a porous adsorbent and a noble metal catalyst, as described in the second modification example of the third embodiment. In this case, it is appropriate that an air blower for supplying the odorant removal portion with
10 oxygen gas be added, and that the odorant removal portion be supplied with oxygen gas during an operation stoppage period (i.e., a power generation stoppage period) of the fuel cell system. Thus, the physically adsorbed odorant can be oxidized (burnt).

[0086]

The invention is not limited to the aforementioned examples or
15 embodiments and can be implemented in various modes without departing from the gist thereof. For example, the following modifications are possible as well.

[0087]

(1) In the aforementioned embodiments, the fuel cell system includes the circulating pump 250 and the circulation passage 203. However, the fuel
20 cell system may dispense with the circulating pump 250 and the circulation passage 203.

[0088]

(2) In the aforementioned embodiments, the fuel gas supply portion 200 includes the gas tank 210 for storing the mixed gas (fuel gas) containing
25 hydrogen gas and the odorant. Instead, however, the fuel gas supply portion 200 may include a gas tank for storing hydrogen gas, and an odorant addition portion for adding an odorant to hydrogen discharged from the gas tank so as to generate the mixed gas (fuel gas). In the case where the fuel gas supply portion includes the odorant addition portion, the fuel gas supply portion may include a hydrogen-
30 occlusion alloy or may be provided with a reformation portion for generating hydrogen gas by reforming alcohol, natural gas, gasoline, ether, aldehyde and the like.

[0089]

In general, it is appropriate that a fuel gas containing hydrogen gas and an odorant be introduced into the fuel cell.

[0090]

(3) In the aforementioned embodiments, butyric acid is used as the odorant that is unlikely to deteriorate output characteristics of the fuel cell. Instead, however, diethyl sulfide or the like can also be used.

5

[0091]

In the present specification, the odorant that is unlikely to deteriorate output characteristics of the fuel cell refers to an odorant satisfying a condition as mentioned below. First of all, a comparison is made between a first case where the fuel cell is supplied with a fuel gas containing only hydrogen gas and a second case where the fuel cell is supplied with a fuel gas containing hydrogen gas and an odorant. The aforementioned odorant that is unlikely to deteriorate output characteristics of the fuel cell refers to an odorant in which an output current value of the fuel cell in the second case is about 90% or more of an output current value of the fuel cell in the first case. An output current value is measured after the lapse of a power generation period of 24 hours with a predetermined load being connected to the fuel cell and with the fuel cell being supplied with a sufficient amount of the fuel gas and a sufficient amount of the oxidative gas.

10
15

[0092]

(4) In the aforementioned embodiments, the odorant removal portion includes the porous adsorbent that removes the odorant from the mixed gas by physically adsorbing the odorant. Instead, however, the odorant removal portion may include an adsorbent that removes the odorant from the mixed gas by chemically adsorbing the odorant. In the case where the odorant is TBM, it is appropriate that the odorant removal portion include an adsorbent such as ZnO or the like. It is to be noted herein that physical adsorption means adsorption resulting from a Van der Waals force, and that chemical adsorption means adsorption resulting from chemical bonding.

20

25

[0093]

In the aforementioned embodiments, the odorant removal portion adsorbs the odorant. Instead, however, the odorant removal portion may absorb the odorant. In this case as well, the odorant removal portion can remove the odorant from the mixed gas. It is to be noted herein that absorption means a phenomenon of penetration of gas molecules into a liquid or a solid, and that adsorption means a phenomenon of residence of gas molecules in the vicinity of a surface of a liquid or a

30

solid. In particular, a phenomenon of absorption of gas molecules into a solid is referred to as occlusion.

[0094]

Furthermore, the odorant removal portion may include a reactive agent
5 reacting with the odorant, instead of the adsorbent. In the case where the odorant is butyric acid, it is appropriate that the odorant removal portion include, for example, a pellet containing a basic substance. Calcium hydroxide, aluminum hydroxide or the like can be used as the basic substance.

[0095]

10 As described above, the odorant removal portion may include a noble metal catalyst such as Pt or the like in addition to or instead of a porous adsorbent.

[0096]

In general, it is appropriate that an odorant removal portion be capable
of removing an odorant from a mixed gas containing hydrogen gas and the odorant.

15 [0097]

(5) In the aforementioned embodiments, the odorant removal
portion is provided in the different portions of the fuel cell system. However, the odorant removal portion may be provided somewhere else.

[0098]

20 In general, it is appropriate that an odorant removal portion remove an odorant after a fuel gas containing hydrogen gas and the odorant has been introduced into a fuel cell.

[0099]

25 (6) Although the aforementioned embodiments deal with cases where the invention is applied to a polymer electrolyte fuel cell, the invention is also applicable to fuel cells of other types.

[BRIEF DESCRIPTION OF THE DRAWINGS]

30 [Fig. 1] Fig. 1 is an explanatory view of an overall construction of a fuel cell system in accordance with a first embodiment of the invention.

[Fig. 2] Fig. 2 is an explanatory view schematically showing an electric cell structure inside a fuel cell 100 shown in Fig. 1.

[Fig. 3] Fig. 3 is an explanatory view schematically showing an internal structure of an odorant removal portion 510 shown in Fig. 1.

[Fig. 4] Fig. 4 is an explanatory view showing a method of manufacturing the odorant removal portion 510 shown in Fig. 3.

[Fig. 5] Fig. 5 is an explanatory view showing an overall construction of a fuel cell system in accordance with a second embodiment of the invention.

[Fig. 6] Fig. 6 is an explanatory view showing an overall construction of a fuel cell system in accordance with a third embodiment of the invention.

[Fig. 7] Fig. 7 is an explanatory view showing an overall construction of a fuel cell system in accordance with a first modification example of the third embodiment.

[Fig. 8] Fig. 8 is an explanatory view schematically showing an internal construction of a fuel cell 100C shown in Fig. 7.

[Fig. 9] Fig. 9 is an explanatory view showing an overall construction of a fuel cell system in accordance with a fourth embodiment of the invention.

[Fig. 10] Fig. 10 is an explanatory view showing an overall construction of a fuel cell system in accordance with a modification example of the fourth embodiment.

[Fig. 11] Fig. 11 is an explanatory view schematically showing an electric cell structure inside a fuel cell 100D shown in Fig. 10.

[Fig. 12] Fig. 12 is an explanatory view showing an overall construction of a fuel cell system in accordance with a fifth embodiment of the invention.

[Fig. 13] Fig. 13 is an explanatory view schematically showing a stack structure inside a fuel cell 100E shown in Fig. 12.

[Fig. 14] Fig. 14 is an explanatory view schematically showing an electric cell structure inside a fuel cell in accordance with a first modification example of the fifth embodiment.

[DESCRIPTION OF THE REFERENCE NUMERALS]

100, 100C, D, E, E1: FUEL CELLS

101 TO 103: STACKS

110: SINGLE CELL

112: ELECTROLYTE MEMBRANE

114a: ANODE (HYDROGEN POLE)

114c: CATHODE (OXYGEN POLE)

116a, 116c: CATALYTIC LAYERS

120: SEPARATOR

- 121: ANODE-SIDE PASSAGE (SMALL PASSAGE)
- 122: CATHODE-SIDE PASSAGE (SMALL PASSAGE)
- 131: FIRST BRANCH PIPES
- 132: SECOND BRANCH PIPES
- 5 200: FUEL GAS SUPPLY PORTION
- 201: FUEL GAS PASSAGE
- 202: FUEL OFF GAS PASSAGE
- 203: CIRCULATION PASSAGE
- 210: GAS TANK
- 10 221: PRESSURE REDUCING VALVE
- 222: FLOW CONTROL VALVE
- 240: GAS-LIQUID SEPARATION PORTION
- 250: CIRCULATING PUMP
- 260: SHUT-OFF VALVE
- 15 290: AIR BLOWER
- 300: OXIDATIVE GAS SUPPLY PORTION
- 301: OXIDATIVE GAS PASSAGE
- 302: OXIDATIVE OFF GAS PASSAGE
- 310: AIR BLOWER
- 20 401: CONFLUENT OFF GAS PASSAGE
- 510: ODORANT REMOVAL PORTION
- 512: CARRIER
- 512a: FLAT PLATE
- 512b: CORRUGATED PLATE
- 25 512c: AXIAL MEMBER
- 520: ODORANT REMOVAL PORTION
- 530, 530A: ODORANT REMOVAL PORTIONS
- 540, 542: ODORANT REMOVAL PORTIONS
- 550, 550A: ODORANT REMOVAL PORTIONS
- 30 600: CONTROL PORTION

[NAME OF THE DOCUMENT] ABSTRACT OF THE DISCLOSURE

[ABSTRACT]

[TASK] To provide an art for enlarging a range in which leakage of hydrogen gas can be sensed in a fuel cell.

5 [MEANS OF SOLVING THE PROBLEM]

10 A fuel cell system includes a fuel cell (100), a fuel gas passage (201) through which a fuel gas containing an odorant and hydrogen gas supplied to the fuel cell flows, an oxidative gas passage (301) through which an oxidative gas supplied to the fuel cell flows, a fuel off gas passage (202) through which a fuel off gas discharged from the fuel cell flows, an oxidative off gas passage (303) through which an oxidative off gas discharged from the fuel cell flows, and an odorant removal portion (510) provided in the fuel off gas passage. The odorant removal portion removes the odorant after the fuel gas has been introduced into the fuel cell.

[SELECTED DRAWING] FIG. 1

15

[NAME OF THE DOCUMENT] DRAWINGS

Fig. 1

- (1) ... FUEL GAS
- (2) ... FUEL OFF GAS
- 5 (3) ... OXIDATIVE GAS
- (4) ... OXIDATIVE OFF GAS
- (5) ... TO THE ATMOSPHERE
- 100 ... FUEL CELL
- 210 ... GAS TANK
- 10 240 ... GAS-LIQUID SEPARATION PORTION
- 510 ... ODORANT REMOVAL PORTION
- 600 ... CONTROL PORTION

Fig. 5

- 15 (1) ... FUEL GAS
- (2) ... FUEL OFF GAS
- (3) ... OXIDATIVE GAS
- (4) ... OXIDATIVE OFF GAS
- (5) ... TO THE ATMOSPHERE
- 20 100 ... FUEL CELL
- 210 ... GAS TANK
- 240 ... GAS-LIQUID SEPARATION PORTION
- 520 ... ODORANT REMOVAL PORTION
- 600 ... CONTROL PORTION

25

Fig. 6

- (1) ... FUEL GAS
- (2) ... FUEL OFF GAS
- (3) ... OXIDATIVE GAS
- 30 (4) ... OXIDATIVE OFF GAS
- (5) ... TO THE ATMOSPHERE
- (6) AIR
- 100 ... FUEL CELL

210 ... GAS TANK
240 ... GAS-LIQUID SEPARATION PORTION
530 ... ODORANT REMOVAL PORTION
600 ... CONTROL PORTION

5

Fig. 7

(1) ... FUEL GAS
(2) ... FUEL OFF GAS
(3) ... OXIDATIVE GAS
10 (4) ... OXIDATIVE OFF GAS
(5) ... TO THE ATMOSPHERE

100C ... FUEL CELL

210 ... GAS TANK
240 ... GAS-LIQUID SEPARATION PORTION
15 600 ... CONTROL PORTION

Fig. 8

(1) ... FUEL GAS
(2) ... FUEL OFF GAS
20 (3) ... OXIDATIVE OFF GAS
500 ... ODORANT REMOVAL PORTION

Fig. 9

(1) ... FUEL GAS
25 (2) ... FUEL OFF GAS
(3) ... OXIDATIVE GAS
(4) ... OXIDATIVE OFF GAS
(5) TO THE ATMOSPHERE
100 ... FUEL CELL
30 210 ... GAS TANK
240 ... GAS-LIQUID SEPARATION PORTION
540 ODORANT REMOVAL PORTION
600 ... CONTROL PORTION

Fig. 10

- (1) ... FUEL GAS
- (2) ... FUEL OFF GAS
- (3) ... OXIDATIVE GAS
- 5 (4) ... OXIDATIVE OFF GAS
- (5) ... TO THE ATMOSPHERE
- 100D ... FUEL CELL
- 210 ... GAS TANK
- 240 ... GAS-LIQUID SEPARATION PORTION
- 10 540 ... ODORANT REMOVAL PORTION
- 600 ... CONTROL PORTION

Fig. 12

- (1) ... FUEL GAS
- 15 (2) ... FUEL OFF GAS
- (3) ... OXIDATIVE GAS
- (4) ... OXIDATIVE OFF GAS
- (5) ... TO THE ATMOSPHERE
- 100E ... FUEL CELL
- 20 210 ... GAS TANK
- 240 ... GAS-LIQUID SEPARATION PORTION
- 600 ... CONTROL PORTION

Fig. 13

- 25 (1) ... FUEL GAS
- (2) ... FUEL OFF GAS

30